



Proceq Ground Penetrating Radars

GP8000

Faster, easier concrete inspections and structural imaging with SFCW ground penetrating radar technology



Resolution & depth

Superior depth and clarity of data thanks to the unique Swiss Made radar technology with all the frequencies you'll ever need. Immediate insights with 3D and Augmented Reality.



Powerful UI

Inspect with ease of use, from the tightest spots to the tallest walls to the longest streets. Superior ergonomics to tackle any challenge with comfort, without cables.



Great handling

Mobile app that lets you annotate measurements with voice, photos and comments. Generate reports and share them instantly. Access your data from anywhere, anytime.



Software / Workspace App

Superline Scan (1000m / 3281 ft) Area Scan (with Flexible Grid up to 100m2 / 1076 ft2) Superline scan¹ A-scan (incl. envelope) Migrated view Non-migrated view Split view¹ Time-Slice view² Basic 3D view AR Argumented Reality (AR) Workspace integration Automatic Logbook Reporting Export formats Display Unit Specs*: Superline Scan (1000m / 3281 ft) Area Scan (with Flexible Grid up to 100m2 /		
A-scan (incl. envelope) Migrated view Non-migrated view Split view¹ Time-Slice view² Basic 3D view AR Advanced visualization Advanced visualization Reporting Fig. 1 Fig. 2 Fig. 3 Fig. 2 Fig. 2 Fig. 3 Fig. 4 Fig. 2 Fig. 2 Fig. 4 Fig. 2 Fig. 4 Fig. 2 Fig. 4 Fig. 2 Fig. 4 Fig.	Measurement modes	Area Scan (with Flexible Grid up to 100m2 /
Advanced visualization Augmented Reality (AR) Workspace integration Automatic Logbook SEG-Y export Instant report generation Share via URL JPG PNG Export formats CSV SEGY HTML Latest Apple® iPad recommended (iPad with iOS 11.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer	Review modes	A-scan (incl. envelope) Migrated view Non-migrated view Split view¹ Time-Slice view² Basic 3D view
Automatic Logbook SEG-Y export Instant report generation Share via URL JPG PNG CSV SEGY HTML Latest Apple® iPad recommended (iPad with iOS 11.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer	Advanced visualization	3D view
Export formats CSV SEGY HTML Latest Apple® iPad recommended (iPad with iOS 11.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer	Reporting	Automatic Logbook SEG-Y export Instant report generation
(iPad with iOS 11.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer	Export formats	PNG CSV SEGY
LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer	Display Unit Specs*:	(iPad with iOS 11.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide
	Display Unit Sensors*:	LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer







SWISS MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors. www.screeningeagle.com

Request a quote





Processing Unit / Sensor

Radar technology	Stepped-frequency continuous-wave (SFCW) GPR
Modulated frequency range	200 – 4000 MHz
Penetration depth	80 cm / 31.5 in
Battery	Flight-safe, removable pack, 8x AA (NiMH)
Dimensions	22.1 x 18 x 14 cm 8.7 x 7.1 x 5.5 in
Weight	1.5 kg / 3.3 lbs (excl. battery pack)
Ground clearance	0.8 cm / 0.32 in
Antennas	1
Antenna distance to edge	8.3 cm / 3.27 in
Special features	All-wheel drive with high-traction wheels Laser light guidance
Connections	Wi-Fi (802.11n) to display unit
Autonomy	3 h