







# ECO-FRIENDLY CARTRIDGE FILTERS FOR THE FINEST FILTRATION

# **1** ULTRA-FINE FILTRATION

A filtration level of between 15 and 20 microns, 2 times finer than sand filters, for translucent water in all circumstances and **optimal bathing comfort**.

# 2 SIMPLE AND WATER EFFICIENT

No need for backwashes, simply rinse the cartridge with fresh water. What's more, you will **use at least 10 times less water** than when cleaning a sand filter.

# **3** SUITABLE FOR ALL INSTALLATIONS

Very compact filter for **easy installation** in all types of technical rooms, and particularly when there is no drain possibility. Installation is even quicker thanks to the Versa Plumb<sup>®</sup> kit that is available as an optional accessory when using any FloPro<sup>™</sup> pump model.








| TECHNICAL INFORMATION                 |  |                                       |
|---------------------------------------|--|---------------------------------------|
|                                       | C\$100   | CS150                                 |
| Maximum filtration capacity (8hr/day) | 130 m <sup>3</sup>   | 170 m <sup>3</sup>                    |
| Max. flow rate (m³/h)                 | 22.7   | 34.1                                  |
| Filter area (m²)                      | 9.3  | 14.0                                  |
| Number of layers (cartridge)          | 143  | 215                                   |
| Filtration speed per m <sup>2</sup>   | 2.4 m <sup>3</sup> /hr/m <sup>2</sup>  | 2.1 m <sup>3</sup> /hr/m <sup>2</sup> |
| Diameter of threaded connections      | 63/50 mm   |                                       |
| Working pressure (bar or kg/cm²)      | 0.2 to 0.8 (variable speed pump) / 0.4 to 1.2 (single speed pump)                                    |                                       |
| Maximum pressure (bar or kg/cm²)      | 3.5  |                                       |
| Tank material                         | Glass-fibre reinforced polyester body, 100% chemical corrosion resistant                             |                                       |
| Filtration fineness                   | 15-20 microns  |                                       |
| Pressure gauge position               | On top of the lid  |                                       |
| Drain                                 | Extra-large drain with a useful diameter of 63 mm (supplied with union connector for drainage pipes) |                                       |

#### **BENEFITS**

- Ultra-compact footprint.
- Large drain for water which can be connected to a discharge pipe.



## STANDARD FEATURES





63/50mm union tailpieces

Filter cartridge

RCS Paris 395 068 679 - © Crédits photos : Zodiac<sup>®</sup> - Zodiac<sup>®</sup> is a registered trademark of Zodiac International, S.A.S.U., used under license - www.le-fil.fr - Ref. : WL15735

#### ACCESSORY

- Versa Plumb<sup>®</sup> connection kit:
  - quick installation with a FloPro<sup>™</sup> pump (all models)
  - improved hydraulic efficiency
  - 1/2" thread for earth connection kit



## FOR WHICH TYPE OF POOLS?

- 1 ALL TYPES OF SWIMMING POOL

2 POOLS UP TO 170 M<sup>3</sup>







### www.zodiac-poolcare.com