## 50 mL Gastight Syringe Model 1050 TLL, PTFE Luer Lock, Needle Sold Separately

Specification Sheet (Part/REF # 85020)



The 1000 series syringes are a mid-volume Gastight syringe. This series of syringes is ideal for dispensing volumes from 1 mL up to 100 mL. A variety of different terminations and needle options are available in this series.

## **Product Specifications**

•	
Volume	50 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	Borosilicate glass, PTFE, PCTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	100 psig (6.9 bar)
Maximum Temperature	80°C / 176°F
Maximum Temperature Minimum Temperature	
	80°C / 176°F
Minimum Temperature	80°C / 176°F 10°C / 50°F
Minimum Temperature  Barrel Inner Diameter	80°C / 176°F 10°C / 50°F 1.28 inches (32.6 mm)
Minimum Temperature  Barrel Inner Diameter  Barrel Outer Diameter	80°C / 176°F 10°C / 50°F 1.28 inches (32.6 mm) 1.45 inches (36.9 mm)

Specifications are subject to change without notice

Spec. Version B

 $\underline{https://www.hamiltoncompany.com/laboratory-products/syringes/85020}$