- Durable Housing for Harsh Environments
- Accurate Temperature and Fan Speed Regulation
- Units Available for **Heating and Cooling Applications**



Line Voltage Thermostat and Fan Control

Our weatherproof Line Voltage Thermostats and Fan Controls are designed to accurately regulate precise temperature and fan speed in commercial, industrial, and agricultural settings.



KJ16110-A

Heat & Cool

30°F to 110°F

±2° accuracy, 3° differential

Weatherproof Stainless Steel Sens

- Portable / Pre-Wired Line **Voltage Thermostats**
- 8 Foot Cord with Piggyback

- Fan Controls
- For use with variable speed fans
- Ability to control 3-5 fans- Portable / Pre-Wired Units Available



SENASYS

704 Bartlett Ave., Altoona, WI 54720

ADJUSTMENT RANGE

FUNCTION

ACCURACY

FEATURES UL LISTED

FULL LOAD AMPS Voltage AC — 120 / 208 / 240

> 8' HSJ CORD w/ PIGGYBACK PLUG

Portable Line Voltage Thermostats and Fan Controls

LINE VOLTAGE THERMOSTATS

KT16110 BASIC CONSTRUCTION Polycarbonate Housing Polycarbonate Housing Heat & Cool 30°F to 110°F ±2° accuracy, 3° differential Weatherproof Stainless Steel Senso **SWITCH TYPE** Single Stage (SPDT) Two Stage (SPDT/SPDT)

KC12110 Polycarbonate Housing Heat & Cool 30°F to 110°F ±3° accuracy, 3° differential Weatherproof Stainless Steel Sens Single Stage (SPDT)

PortExt8 Heat & Cool 30°F to 110°F ±2° accuracy, 3° differential Weatherproof 5ft Nickel Plated Se Single Stage (SPDT)

KP16110-A Polycarbonate Housing Heat & Cool 30°F to 110°F ±2° accuracy, 3° differential Weatherproof Stainless Steel Senso Single Stage (SPDT)

KF5120 Fan Control Single Stage (SPDT)

KF5120P
Polycarbonate Housing
Fan Control
30% to 100%
On/Off control for shaded pole, PSC and universal
Weatherproof Control 3-5 fans
✓
5A
Single Stage (SPDT)
✓

K-Kontrols, Manufacturered by Senasys | 704 Bartlett Ave., Altoona, WI 54720 Phone: (715) 831-6353 | E-mail: info@senasys.com



FAN CONTROLS