

# 50 mL, Model 1050 TLL SYR, NDL Sold Separately

## Specification Sheet (Part# 85020 )



### Product Specifications

|                         |                                 |
|-------------------------|---------------------------------|
| Volume                  | 50 mL                           |
| Syringe Type            | Gastight                        |
| Syringe Series          | 1000                            |
| Termination             | PTFE Luer Lock (TLL)            |
| Needle                  | Metal (N) or Kel-F              |
| Gauge                   | No Needle Included              |
| Point Style             | No Needle Included              |
| Needle Length           | No Needle Included              |
| Std. Needle Dead Volume | N/A                             |
| Fluid Path              | Borosilicate glass, PTFE, PCTFE |
| Autoclavable            | No                              |
| Gas Sterilizable        | Yes                             |
| Pressure                | 100 psig (6.9 bar)              |
| Maximum Temperature     | 80°C / 176°F                    |
| Minimum Temperature     | 10°C / 50°F                     |
| Barrel Inner Diameter   | 1.28 inches (32.6 mm)           |

## Product Specifications

|                       |                       |
|-----------------------|-----------------------|
| Barrel Outer Diameter | 1.45 inches (36.9 mm) |
| Sales Quantity        | 1 syringe per pack    |

© 2017 Hamilton Company. All Rights Reserved.

All trademarks are owned and/or registered by Hamilton Company in the U.S. and/or other countries.

Revision: A / 2010-05-11 Printed in the U.S.A.

**HAMILTON**  <sup>®</sup>

To find a representative in your area, please visit [hamiltoncompany.com/contacts](http://hamiltoncompany.com/contacts)