


Spindle ball bearings (HY)* SM 61905 C



Precision class P4 / ABEC7

Components

Bearing designation:	(HY)* SM 61905 C
Bearing design:	SM
Series / size:	61905
Ball material:	Steel 100Cr6
Ball material HY :	Ceramic Si3N4
Cage:	TA (TXM available upon request)
Precision:	P4 (HG, UP, P2 upon request)
Main dimensions [d x D x B]:	25 x 42 x 9 mm

Technical data (Standard bearings)

Static load capacity C_0 :	3150
Dynamic load capacity C:	5800
Speed limit n_{Fett} :	44250
Speed limit n_{Oj} :	59000

Technical data (Hybrid bearings)*

Static load capacity C_{0HY} :	2200
Dynamic load capacity C_{HY} :	5800
Speed limit n_{Fett} :	55312.5
Speed limit n_{Oj} :	73750

Pre-tension

Light (L):	30 N
Axial rigidity (C_{ax}):	23 N/ μ m
Medium (M):	90 N
Axial rigidity (C_{ax}):	36 N/ μ m
Heavy (S):	180 N
Axial rigidity (C_{ax}):	49 N/ μ m
Spring preload (Ff):	175 N

The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.

* All ball bearings are also available as hybrid ball bearings (HY).