AG OFCAS 35 PLUS

Air compressor



The high quality of the materials combined with cutting-edge technology of the compressor unit, ensure reliability, professionalism and economy allowing continuous use, unthinkable in traditional direct-drive oil-free compressors.

The AirGen **OFCAS 35 PLUS** is the ideal compressor to supply all Zero Air generators **ZA FID** and **ZA TOTAL** or the high purity Nitrogen generator **NG EOLO**.

Main applications

- Medical laboratories
- Chemical and pharmaceutical industry
- Food factory
- Laser equipments

Main Advantages

- ✓ Ultra silent technology: 58 dB(A)
- ✔ Oil free
- ✓ Low maintenance
- ✓ Smooth running low vibrations
- ✓ Compact
- ✔ Reliable
- Automatic water purge







Specifications



Model: AG OFCAS	35 PLUS
General data	
Rated power (Max)	0.75 kW
Internal tank capacity	10 L
Dimensions (W x D x H)	43 x 75 x 68 cm
Net weight	90 kg
Noise level	58dB(A) @ 1.5 m from front
Air Outlet	
Operation control	Electronic pressure control – Set point with hysteresis
Air Delivery (Max)	35 l/min @ 7Bar
Dew point *1	< -20°C (<-4°F)
Electrical data	
	100-115Vac (±10%) 50/60 Hz
Supply rating	or
	230Vac (±10%) 50/60 Hz
Connection type	IEC320-C14
Nominal power	750W
Fuse rating (5x20mm)	10A (250Vac – T)
Connections	
Compressed Air outlet	1/8" BSPP female fitting
Condensate water drain	1/8" BSPP female fitting
Operating/storage conditions	
Working Temperature	5-40°C (41-104°F)
Storage Temperature	1-50°C (34-122°F)
Humidity (max, non condensing)	80% [5-40°C (41-104°F)]
Heat value	2560
IP rating	IP20
Pollution degree rating	2 (with no aromatic compounds)
Altitude	< 2000m

^{*1} Atmospheric Dew-point (ADP)

Ordering codes Compressor 6920.96.035 Consumable 3709.04.171

AG OFCAS 35 PLUS

Filter elements for OFCAS 35

For further information or to trial the equipment, please contact us:



Tel: **01322 285850**

Email: info@uvison.com

