



EARTH CONTINUITY TESTER

5030EC



Perform earth bonding tests and confirm continuity with reliability and peace of mind with huge safety features in a simple to use all-in-one machine.

Key Features

- Clear and concise display on high brightness VFD
- Invariable current
- Timing test function from 0.5s to 999s randomly set
- Judge via comparison windows
- Touch inspection function
- RS232C, REMOTE and status output interface to make operation ultra-convenient
- Memory backup function

Technical Specifications

MODEL	GPS-5030EC
Test Current	3 ~ 30A
Resistance Value	0 ~ 1.2Ω
Max. Output Power	150VA
Output Voltage	0 - 5.5V
Test Time	0.5 ~ 999s
Resistance Display Accuracy	±5% +20μΩ
Current Display Accuracy	START. STOP, STARTENABLE, HV ON Display
Remote Control	Status Output: PASS, U-FALL, PROTECTION, READY, TEST, HV-ON Control: START, STOP, ENABLE, INTERLOCK
Signal Input & Output Interface	RS232

General Specifications

Dimensions

330 x 150 x 410mm / 13 x 6 x 16.5"
(w x d x h) approx.

Mass

14.0kg/31.0lbs approx.

Services

1-year warranty (subject to product registration with GPS Ltd). Visit www.gpslimited.com/register-product