

ALARM PANEL NFPA

6150-ALM-03



Mission Critical Reliability

The Bird NFPA alarm panel meets all NFPA code requirements for a dedicated alarm panel within the fire command center. To report the status of all RF emitting devices and system component locations, the annunciators are 7 Bicolor LEDs (Green=No Alarm, Red=Alarm), dedicated to the failure modes to annunciate. The monitoring panel provides a clear visual display and labeled indications of the required alarms for a single booster. Alarm triggers are through Form C Contacts on the Booster.

Specifications

SYSTEM

Alarm Input	Form C Dry contacts, Normally closed = green
Connector	RJ-45
Alarm Display	LED
Alarms Displayed	Power Link Status Signal Booster Failure Loss of AC Power Antenna Malfunction Low Battery Charge Fail

ENCLOSURE

Rating	NEMA 4 / IP65
Color	Red

ENVIRONMENTAL

Operating Temperature	32 °F to 122 °F (0 °C to 50 °C)
------------------------------	---------------------------------

PHYSICAL

Size	6.0 in x 8.0 in x 3.5 in (153 mm x 203 mm x 89 mm)
Weight	7.0 lb (3.18 kg)

birdrf.com/products

The **RF** Experts | USA Sales : 30303 Aurora Rd, Solon, OH 44139 | www.birdrf.com
Phone: +1 440.248.1200 / 866.695.4569 [Toll Free] | Fax: +1 440.248.5426 / 866.546.4306 [Toll Free]