



Commercial Lighting



Industrial Lighting



Sports Lighting

MLLG-AG-LED-ST1 Street Light Product Family



**Why
contractors
choose us**



Free Lighting
Plans to ensure
customer
satisfaction



Dedicated
Lighting
Specialist for
each project



Large
inventory of
LED Lights

Table of Contents

	Page Number
30 Watt LED Cobra Head Street Light 3600 Lumens 5000K 100-277V - MLLG-AG-LED-ST1-30	3
- MLLG-AG-LED-ST1-50	4
- MLLG-AG-LED-ST1-70	5
- MLLG-AG-LED-ST1-90	6
- MLLG-AG-LED-ST1-120	7
- MLLG-AG-LED-ST1-150	8
- MLLG-AG-LED-ST1-180	9

30 Watt LED Cobra Head Street Light | 3600 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AG-LED-ST1-30 **Web ID:** 1484

30 Watt LED STREET LIGHT produces 3600 lumens at 120 lumens / watt replacing 100 Watt Metal Halide and has durable die-cast aluminum housing. Optic include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable driver at 100V-277V. Color Temperature is 4000K or 5000K. Tool free maintenance and access so installation and maintenance is simple and easy. Fixture also includes Power-Off protection for maintenance safety. Photocell is available if you need one. 10 kVa surge protection included.

This fixture is mounted on a 2 3/8 in pole. Fixture has internal clamps to secure itself to pole. Access to fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP66 Wet location rated and can operate in temperatures ranging from -22 F to 122 F. This fixture has 1000 hours salt water spray test. Fixture is tough and durable and is IK08 impact rated.

Product Specifications

Watts:	30	Dimmable:	1-10V
Lumens:	3600	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	120	Frequency:	50-60Hz
Replaces:	100 Watt Metal Halide	Power Factor:	> .93
Color Temp:	4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP65 - Aluminum Alloy and PC Lens
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	30.03 X 13.85 X 8.85
Input Voltage:	100V-277V	Weight:	18.73
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	50,000 (L70) hours		

50 Watt LED Cobra Head Street Light | 6000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AG-LED-ST1-50 **Web ID:** 1485

50 Watt LED STREET LIGHT produces 6000 lumens at 120 lumens / watt replacing 150 Watt Metal Halide and has durable die-cast aluminum housing. Optic include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable driver at 100V-277V. Color Temperature is 4000K or 5000K. Tool free maintenance and access so installation and maintenance is simple and easy. Fixture also includes Power-Off protection for maintenance safety. Photocell is available if you need one. 10 kVa surge protection included.

This fixture is mounted on a 2 3/8 in pole. Fixture has internal clamps to secure itself to pole. Access to fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP66 Wet location rated and can operate in temperatures ranging from -22 F to 122 F. This fixture has 1000 hours salt water spray test. Fixture is tough and durable and is IK08 impact rated.

Product Specifications

Watts:	50	Dimmable:	1-10V
Lumens:	6000	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	120	Frequency:	50-60Hz
Replaces:	150 Watt Metal Halide	Power Factor:	> .93
Color Temp:	4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP65 - Aluminum Alloy and PC Lens
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	30.03 X 13.85 X 8.85
Input Voltage:	100V-277V	Weight:	18.73
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	50,000 (L70) hours		

70 Watt LED Cobra Head Street Light | 8400 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AG-LED-ST1-70 **Web ID:** 1486

70 Watt LED STREET LIGHT produces 8400 lumens at 120 lumens / watt replacing 250 Watt Metal Halide and has durable die-cast aluminum housing. Optic include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable driver at 100V-277V. Color Temperature is 4000K or 5000K. Tool free maintenance and access so installation and maintenance is simple and easy. Fixture also includes Power-Off protection for maintenance safety. Photocell is available if you need one. 10 kVa surge protection included.

This fixture is mounted on a 2 3/8 in pole. Fixture has internal clamps to secure itself to pole. Access to fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP66 Wet location rated and can operate in temperatures ranging from -22 F to 122 F. This fixture has 1000 hours salt water spray test. Fixture is tough and durable and is IK08 impact rated.

Product Specifications

Watts:	70	Dimmable:	1-10V
Lumens:	8400	Beam Angle:	Type 2,3,4,5
Lumens/Watt:	120	Frequency:	50-60Hz
Replaces:	250 Watt Metal Halide	Power Factor:	> .93
Color Temp:	4000K 5000K	THD:	< 20%
CRI:	70+	Housing:	IP65 - Aluminum Alloy and PC Lens
IP Rating:	IP66	Mounting:	Pole
IK Rating:	IK08	Dimensions:	30.03 X 13.85 X 8.85
Input Voltage:	100V-277V	Weight:	18.73
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	50,000 (L70) hours		

90 Watt LED Cobra Head Street Light | 10800 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AG-LED-ST1-90 **Web ID:** 1487

90 Watt LED STREET LIGHT produces 10800 lumens at 120 lumens / watt replacing 250 Watt Metal Halide and has durable die-cast aluminum housing. Optic include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable driver at 100V-277V. Color Temperature is 4000K or 5000K. Tool free maintenance and access so installation and maintenance is simple and easy. Fixture also includes Power-Off protection for maintenance safety. Photocell is available if you need one. 10 kVa surge protection included.

This fixture is mounted on a 2 3/8 in pole. Fixture has internal clamps to secure itself to pole. Access to fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP66 Wet location rated and can operate in temperatures ranging from -22 F to 122 F. This fixture has 1000 hours salt water spray test. Fixture is tough and durable and is IK08 impact rated.

Product Specifications

DLC Model:	MLLG-AG-LED-ST1-90-4	Dimmable:	1-10V
Watts:	90	Beam Angle:	Type 2,3,4,5
Lumens:	10800	Frequency:	50-60Hz
Lumens/Watt:	120	Power Factor:	> .93
Replaces:	250 Watt Metal Halide	THD:	< 20%
Color Temp:	4000K 5000K	Housing:	IP65 - Aluminum Alloy and PC Lens
CRI:	70+	Mounting:	Pole
IP Rating:	IP66	Dimensions:	30.03 X 13.85 X 8.85
IK Rating:	IK08	Weight:	18.73
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-22°F to +122°F		
Rated Life:	50,000 (L70) hours		

120 Watt LED Cobra Head Street Light | 14400 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AG-LED-ST1-120 **Web ID:** 1488

120 Watt LED STREET LIGHT produces 14400 lumens at 120 lumens / watt replacing 400 Watt Metal Halide and has durable die-cast aluminum housing. Optic include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable driver at 100V-277V. Color Temperature is 4000K or 5000K. Tool free maintenance and access so installation and maintenance is simple and easy. Fixture also includes Power-Off protection for maintenance safety. Photocell is available if you need one. 10 kVa surge protection included.

This fixture is mounted on a 2 3/8 in pole. Fixture has internal clamps to secure itself to pole. Access to fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP66 Wet location rated and can operate in temperatures ranging from -22 F to 122 F. This fixture has 1000 hours salt water spray test. Fixture is tough and durable and is IK08 impact rated.

Product Specifications

DLC Model:	MLLG-AG-LED-ST1-120-4	Dimmable:	1-10V
Watts:	120	Beam Angle:	Type 2,3,4,5
Lumens:	14400	Frequency:	50-60Hz
Lumens/Watt:	120	Power Factor:	> .93
Replaces:	400 Watt Metal Halide	THD:	< 20%
Color Temp:	4000K 5000K	Housing:	IP65 - Aluminum Alloy and PC Lens
CRI:	70+	Mounting:	Pole
IP Rating:	IP66	Dimensions:	30.03 X 13.85 X 8.85
IK Rating:	IK08	Weight:	18.73
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-22°F to +122°F		
Rated Life:	50,000 (L70) hours		

150 Watt LED Cobra Head Street Light | 18000 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AG-LED-ST1-150 **Web ID:** 1489

150 Watt LED STREET LIGHT produces 18000 lumens at 120 lumens / watt replacing 400 Watt Metal Halide and has durable die-cast aluminum housing. Optic include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable driver at 100V-277V. Color Temperature is 4000K or 5000K. Tool free maintenance and access so installation and maintenance is simple and easy. Fixture also includes Power-Off protection for maintenance safety. Photocell is available if you need one. 10 kVa surge protection included.

This fixture is mounted on a 2 3/8 in pole. Fixture has internal clamps to secure itself to pole. Access to fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP66 Wet location rated and can operate in temperatures ranging from -22 F to 122 F. This fixture has 1000 hours salt water spray test. Fixture is tough and durable and is IK08 impact rated.

Product Specifications

DLC Model:	MLLG-AG-LED-ST1-150-4	Dimmable:	1-10V
Watts:	150	Beam Angle:	Type 2,3,4,5
Lumens:	18000	Frequency:	50-60Hz
Lumens/Watt:	120	Power Factor:	> .93
Replaces:	400 Watt Metal Halide	THD:	< 20%
Color Temp:	4000K 5000K	Housing:	IP65 - Aluminum Alloy and PC Lens
CRI:	70+	Mounting:	Pole
IP Rating:	IP66	Dimensions:	30.03 X 13.85 X 8.85
IK Rating:	IK08	Weight:	18.73
Input Voltage:	100V-277V	Warranty:	5 years
Operating Temp:	-22°F to +122°F		
Rated Life:	50,000 (L70) hours		

180 Watt LED Cobra Head Street Light | 21600 Lumens | 5000K | 100-277V



Product Details

SKU: MLLG-AG-LED-ST1-180 **Web ID:** 1138

180 Watt LED STREET LIGHT produces 21600 lumens at 120 lumens / watt replacing 400 Watt Metal Halide and has durable die-cast aluminum housing. Optic include Type 2 3 4 5 - perfect for street lighting and parking lots. It comes with a 1-10V dimmable driver at 100V-277V. Color Temperature is 4000K or 5000K. Tool free maintenance and access so installation and maintenance is simple and easy. Fixture also includes Power-Off protection for maintenance safety. Photocell is available if you need one. 10 kVa surge protection included.

This fixture is mounted on a 2 3/8 in pole. Fixture has internal clamps to secure itself to pole. Access to fixture is tool free and power-off protection ensures safety during installation and maintenance. It is IP66 Wet location rated and can operate in temperatures ranging from -22 F to 122 F. This fixture has 1000 hours salt water spray test. Fixture is tough and durable and is impact rated.

Product Specifications

DLC Model:	MLLG-AG-LED-ST1-180-4	Dimmable:	1-10V
Watts:	180	Beam Angle:	Type 2,3,4,5
Lumens:	21600	Frequency:	50-60Hz
Lumens/Watt:	120	Power Factor:	> .93
Replaces:	400 Watt Metal Halide	THD:	< 20%
Color Temp:	4000K 5000K	Housing:	IP65 - Aluminum Alloy and PC Lens
CRI:	70+	Mounting:	Pole
IP Rating:	IP66	Dimensions:	30.03 X 13.85 X 8.85
Input Voltage:	100V-277V	Weight:	18.73
Operating Temp:	-22°F to +122°F	Warranty:	5 years
Rated Life:	50,000 (L70) hours		