

UF UTILITY FIXTURES

Utility UV Fixtures are available with flat, A-shaped or half-round reflectors for general-purpose air and surface sterilization. Various sizes and configurations are available for all applications. The UF germicidal UV fixtures can be mounted to walls and ceilings, inside cabinets and equipment and under counters.



All American Air & Water utility fixtures are UL approved and can be ceiling mounted or suspended. Standard electrical operation is 120V 60Hz with other voltages also available.

Benefits

- Direct air and surface sterilization
- Spectrally polished reflectors to maximize UVC lamp output
- 17"-37" fixture lengths
- Single and dual lamp configurations
- Standard and High Output UV fixtures available (only standard output models shown here)
- Simple, tool-free lamp change

Length	Part #	Description	Price Each	
	Utility industrial strip fixture (37" L x 3-1/8" W x 3-7/8" D)			
	UF-36	Single slimline (GML005) lamp	Call	
	UF-36-2	Double slimline (GML005) lamps	Call	
	UF-30-H	Single hot cathode (GML220) lamp	Call	
	Utility fixture with A-shaped reflector (37" L x 9" W x 5" D)			
	UFA-36	Single slimline (GML005) lamp	Call	
	UFA-36-2	Double slimline (GML005) lamps	Call	
37"	UFA-30-H	Single hot cathode (GML220) lamp	Call	
	Utility fixture with half-round reflector (37" L x 3-1/8" W x 5-3/8" D)			
	UFR-36	Single slimline (GML005) lamp	Call	
	UFR-36-2	Double slimline (GML005) lamps	Call	
	UFR-30-H	Single hot cathode (GML220) lamp	Call	
	Utility fixture with guard rails (37" L x 3-3/4" W x 4-1/2" D)			
	GR-36	Single slimline (GML005) lamp	Call	
	GR-36-2	Double slimline (GML005) lamps	Call	
	Utility industrial strip fixture (19" L x 3-1/8" W x 3-7/8" D)			
19"	UF-25H	Single hot cathode (GML215) lamp	Call	
	UF-15-H	Single hot cathode (GML210) lamps	Call	



UF UTILITY FIXTURES

(continued)

	Utility fixture with A-shaped reflector (19" L x 9" W x 5" D)				
	UFA-25H	Single hot cathode (GML215) lamp Call			
	UFA-15H Single hot cathode (GML210) lamps Call				
	Utility fixture with half-round reflector (19" L x 3-1/8" W x 5-3/8" D)				
	UFR-25H	Single hot cathode (GML215) lamp	Call		
	UFR-15H	Single hot cathode (GML210) lamps	Call		
	Utility industrial strip fixture (17" L x 3-1/8" W x 3-7/8" D)				
17"	UF-10-SL	17 x 31/2 x 31/2 n/a	Call		
	UHA-10-SL	17 x 9 x 5 "A" reflector	Call		
	UFR-10-SL	17 x 31/8 x 53/8 half-round reflector	Call		
	Utility industrial strip fixture (14-7/8" L x 2" W x 2" D)				
15"	UF-12-BP	Single slimline (GML125) lamp	Call		
	Utility fixture with A-shaped reflector (14-1/2" L x 2" W x 2" D)				
	UFA-12-BP	Single slimline (GML125) lamp	Call		
	Utility fixture with half-round reflector (14-7/8" L x 28" W x 2" D)				
	UFR-12-BP	Single slimline (GML125) lamp	Call		
	Utility industrial strip fixture (12-1/2" L x 2" W x 2" D)				
	UF-8-H	Single hot cathode (GML105) lamp	Call		
	Utility fixture with A-shaped reflector (12-1/2" L x 3" W x 3" D)				
12"	UFA-8-H	Single hot cathode (GML105) lamp	Call		
	Utility fixture with half-round reflector (12-1/2" L x 2" W x 2" D)				
	UFR-8-H	Single hot cathode (GML105) lamp	Call		
	Utility industrial strip fixture (9-1/4" L x 2" W x 2" D)				
	UF-6-H	Single hot cathode (GML195) lamp	Call		
	Utility fixture with A-shaped reflector (9-1/4" L x 3" W x 3" D)				
9"	UFA-6-H	Single hot cathode (GML195) lamp	Call		
	0FA-0-FI				
		Utility fixture with half-round reflector (9-1/4	·		
	UFR-6-H	Single hot cathode (GML195) lamp	Call		
	Utility industrial strip fixture (6-1/4" L x 2" W x 2" D)				
	UF-4-H	Single hot cathode (GML180) lamp	Call		
6"	Utility fixture with A-shaped reflector (6-1/4" L x 3" W x 3" D)				
Ŭ	UFA-4-H	Single hot cathode (GML180) lamp	Call		
	Utility fixture with half-round reflector (6-1/4" L x 2" W x 2" D)				
	UFR-4-H	Single hot cathode (GML180) lamp	Call		