

Stationary bridging steps

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.



Product features

Load capacity: max. 300 kg
 Max. load per tread: 150 kg
 Platform length: 600 mm
 Standards: EN ISO 14122
 Warranty: 10 years

Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

Product variants

Order number	Clear height, stationary	Inclination	Number of treads	Overall span	Tread width
40355933	740 mm	45 °	4	2431 mm	600 mm
40355934	950 mm	45 °	5	2851 mm	600 mm
40355935	1170 mm	45 °	6	3291 mm	600 mm
40355936	1380 mm	45 °	7	3711 mm	600 mm
40355937	1600 mm	45 °	8	4151 mm	600 mm
40355938	1810 mm	45 °	9	4571 mm	600 mm
40355939	2030 mm	45 °	10	5011 mm	600 mm
40355940	2240 mm	45 °	11	5431 mm	600 mm
40355943	740 mm	45 °	4	2431 mm	800 mm
40355944	950 mm	45 °	5	2851 mm	800 mm
40355945	1170 mm	45 °	6	3291 mm	800 mm
40355946	1380 mm	45 °	7	3711 mm	800 mm
40355947	1600 mm	45 °	8	4151 mm	800 mm



Order number	Clear height, stationary	Inclination	Number of treads	Overall span	Tread width
40355948	1810 mm	45 °	9	4571 mm	800 mm
40355949	2030 mm	45 °	10	5011 mm	800 mm
40355950	2240 mm	45 °	11	5431 mm	800 mm
40355953	740 mm	45 °	4	2431 mm	1000 mm
40355954	950 mm	45 °	5	2851 mm	1000 mm
40355955	1170 mm	45 °	6	3291 mm	1000 mm
40355956	1380 mm	45 °	7	3711 mm	1000 mm
40355957	1600 mm	45 °	8	4151 mm	1000 mm
40355958	1810 mm	45 °	9	4571 mm	1000 mm
40355959	2030 mm	45 °	10	5011 mm	1000 mm
40355960	2240 mm	45 °	11	5431 mm	1000 mm
40355903	880 mm	60 °	4	1915 mm	600 mm
40355904	1130 mm	60 °	5	2203 mm	600 mm
40355905	1380 mm	60 °	6	2492 mm	600 mm
40355906	1630 mm	60 °	7	2781 mm	600 mm
40355907	1880 mm	60 °	8	3069 mm	600 mm
40355908	2130 mm	60 °	9	3358 mm	600 mm
40355909	2380 mm	60 °	10	3647 mm	600 mm
40355910	2630 mm	60 °	11	3935 mm	600 mm
40355913	880 mm	60 °	4	1915 mm	800 mm
40355914	1130 mm	60 °	5	2203 mm	800 mm
40355915	1380 mm	60 °	6	2492 mm	800 mm
40355916	1630 mm	60 °	7	2781 mm	800 mm
40355917	1880 mm	60 °	8	3069 mm	800 mm
40355918	2130 mm	60 °	9	3358 mm	800 mm
40355919	2380 mm	60 °	10	3647 mm	800 mm
40355920	2630 mm	60 °	11	3935 mm	800 mm
40355923	880 mm	60 °	4	1915 mm	1000 mm
40355924	1130 mm	60 °	5	2203 mm	1000 mm
40355925	1380 mm	60 °	6	2492 mm	1000 mm
40355926	1630 mm	60 °	7	2781 mm	1000 mm
40355927	1880 mm	60 °	8	3069 mm	1000 mm
40355928	2130 mm	60 °	9	3358 mm	1000 mm
40355929	2380 mm	60 °	10	3647 mm	1000 mm
40355930	2630 mm	60 °	11	3935 mm	1000 mm