




KP 110

PNEUMATIC ALUMINIUM CORNER CRIMPING MACHINE
PNÖMATİK ALÜMİNYUM KÖŞE BİRLEŞTİRME PRESİ



Bar		Air Cons.	H W			
25 L/ min.	7-10 Bar	Hmax:120 mm Wmax: 150 mm	3500 kg x 2	123x195x131	320	
					350	

GENERAL FEATURES

- It is designed through the pneumatically crimping system
- Cast iron construction of the body that is strong and lasting
- Magnetic tool gripping system that is adjustable according to the shape and height of the profiles
- Special millimeter of scale that allows reading of the positioning value of the knives
- Simultaneous stroke of crimping heads
- Double-acting stroke of bracing clamp appears from the table
- Support arms on the left and right of the machine
- The machine is equipped with the foot pedals for the operation control during the machining cycle
- Hydraulically working 90° of bracing clamp for inner corner
- Operator safety guard
- Operating stroke of knives : 10.5 mm
- Bracing clamp stroke: 80 mm
- Adjustable stroke of knives: from 30 mm to 60 mm

STANDARD ACCESSORIES

- 1 set of 3 mm, 1 set of 5 mm and 1 set of 7 mm crimping knives
- 2x pneumatic vertical clamps
- 2x profil support arms
- 2x allen key (4 and 5 mm)

OPTIONAL ACCESSORIES

- Special crimping knives

GENEL ÖZELLİKLER

- Tamamen pnömatik presleme prensibine sahiptir
- Kuvvetli ve uzun ömürlü dökme demir malzemeden üretilmiş makine gövdesi
- Profillerin şekline ve yüksekliğine göre kolay ayarlanabilir ve monte edilebilir manyetik takım tutma sistemi
- Pozisyonlama ölçülerini okumayı sağlayan milimetrik ölçü skalası
- Birbiri ile senkronize olarak hareket eden presleme kafaları
- Çalışma tablasının altından çıkan merkezleme gönyesi
- Makinenin sağında ve solunda profil destek kolları
- Makine ayak pedalı sayesinde çalışma döngüsünü tamamlamaktadır
- İç köşe 90°destek pistonunun hareketi hidroçek silindir ile olmaktadır
- Operatör güvenlik kapağı
- Operasyon anında bıçakların çalışma stroku : 10.5 mm
- Merkezleme mengene stroku: 80 mm
- Presleme kafalarının ayarlanabilir stroku: 30 mm den 60 mm kadar

STANDART AKSESUARLAR

- 1 set 3 mm, 1 set 5 mm ve 1 set 7 mm kalınlıkta presleme bıçakları
- 2x dikey pnömatik mengene
- 2x profil destek kolu
- 2x alyan anahtarı (4 ve 5 mm)

OPSİYONEL AKSESUARLAR

- Profile özel presleme bıçakları

