

Strip Length	Belt Thickness	Pitch	Order No.
--------------	----------------	-------	-----------

Belt Fastener D71-C
 Special Steel

 Connecting Pin Dia. 1.4 mm
 Minimum Pulley Diameter 25 mm

300 mm	1.5 - 2.0 mm	4 mm	42 101 71 30
600 mm	1.5 - 2.0 mm	4 mm	42 101 71 60
1200 mm	1.5 - 2.0 mm	4 mm	42 101 71 12

Belt Fastener D72-C
 Special Steel

 Connecting Pin Dia. 1.4 mm
 Minimum Pulley Diameter 35 mm

300 mm	2.0 - 2.5 mm	4 mm	42 101 72 30
600 mm	2.0 - 2.5 mm	4 mm	42 101 72 60
1200 mm	2.0 - 2.5 mm	4 mm	42 101 72 12

Belt Fastener D73-C
 Special Steel

 Connecting Pin Dia. 1.4 mm
 Minimum Pulley Diameter 50 mm

300 mm	2.5 - 3.5 mm	4 mm	42 101 73 30
600 mm	2.5 - 3.5 mm	4 mm	42 101 73 60
1200 mm	2.5 - 3.5 mm	4 mm	42 101 73 12


 Material : **Special Steel**

 Box content:
 4 Complete Sets
 (8 Fastener Strips + 4 Connecting Pins)

Note:
 Fasteners D71, D72, D73 can be spliced with the Lacing Tool MATOROLL, Vice Lacer MATOVICE or hydraulic installation machine.

Belt Fastener D71-SS
 Stainless Steel 1.4404

 Connecting Pin Dia. 1.4 mm
 Minimum Pulley Diameter 25 mm

300 mm	1.5 - 2.0 mm	4 mm	42 104 71 30
600 mm	1.5 - 2.0 mm	4 mm	42 104 71 60
1200 mm	1.5 - 2.0 mm	4 mm	42 104 71 12

Belt Fastener D72-SS
 Stainless Steel 1.4404

 Connecting Pin Dia. 1.4 mm
 Minimum Pulley Diameter 35 mm

300 mm	2.0 - 2.5 mm	4 mm	42 104 72 30
600 mm	2.0 - 2.5 mm	4 mm	42 104 72 60
1200 mm	2.0 - 2.5 mm	4 mm	42 104 72 12

Belt Fastener D73-SS
 Stainless Steel 1.4404

 Connecting Pin Dia. 1.4 mm
 Minimum Pulley Diameter 50 mm

300 mm	2.5 - 3.5 mm	4 mm	42 104 73 30
600 mm	2.5 - 3.5 mm	4 mm	42 104 73 60
1200 mm	2.5 - 3.5 mm	4 mm	42 104 73 12


 Material : **Stainless Steel**

 Box content:
 4 Complete Sets
 (8 Fastener Strips + 4 Connecting Pins)

Note:
 Fasteners D71, D72, D73 can be spliced with the Lacing Tool MATOROLL, Vice Lacer MATOVICE or hydraulic installation machine.