

BRW 02 & BRW 08 break-away coupling

Compressed Natural Gas vehicles





Protection of the refuelling line for vehicles powered by compressed natural gas.

Designed to be incorporated in environments in accordance with directives 2014/34/EU (ATEX) and 2014/68/EU.

The break-away system ensures immediate disconnection and automatic shut-off of the circuit if the supply hose is pulled.

Protection for the installation and its users

- Disconnection force specifically configured to prevent accidental disconnection and maintain the integrity of the dispenser and the vehicle.
- Automatic shut-off of the gas distribution circuit on disconnection: prevents gas being released into the atmosphere.
- Immediate disconnection irrespective of the pressure in the hose.

Easy to install and simple to use

- Quick and easy to reconnect using the dedicated reconnection tool.
- Maintenance-free.

Efficiency

As there is no risk of accidental disconnection, prolonged stoppages of installations following unexpected hose pull-outs are prevented and their efficiency is maintained.


Break-Away 08 - 1 function

- Coupling for fast filling of light or heavy vehicles (diagram 1).


Break-Away 02 - 2 functions

- **Venting:** safety when used with a BRW 08 on a fast filling line (diagram 1).
- **Filling:** the Break-Away 02 can also be used on its own by individuals or companies as a coupling for slow filling of light duty vehicles only (diagram 2).

Fast refuelling of light or heavy vehicles: BRW 08 on filling line and BRW 02 on venting line.



Slow refuelling of light vehicles only: BRW 02 only on filling line (no venting line).





Technical data



	Break-Away 08	Break-Away 02
Disconnection force on line (N)	between 225 and 665	between 60 and 220
Possible number of disconnections at 200 bar of air	100	100
Maximum allowable pressure PS (bar)	300	200
Minimum and maximum allowable temperatures TS (°C)	- 40 to + 85	- 40 to + 85

Part numbers

BRW 08

Function and thread	Fitting	Dimensions (mm)		Part numbers
		L	H/flats	
Female thread 	G 3/8	201	24	BRW 08.9102
	G 1/2	207	27	BRW 08.9103
	UN 9/16-18	155	22	BRW 08.9314
	UN 7/8-14	211	32	BRW 08.9322
Reconnection tool 		72		BRW 08.9100

BRW 02

Function and thread	Fitting	Dimensions (mm)		Part numbers
		L	H/flats	
Venting Female thread 	G 1/8	81,5	14	N 007 267 12
	UN 7/16	86,5	17	N 007 316 12
Filling Female thread 	G 1/8	81,5	14	N 001 101 01
	UN 7/16	86,5	17	N 010 310 11



■ Stäubli Units ○ Representatives / Agents

Global presence of the Stäubli Group

www.staubli.com