PRODUCT INFORMATION SHEET



Outdoor Heated Emergency Safety Showers **EXP-EH-5G/45G**

EXP-AH-5G/45G, EXP-EJ-5G/45G



Outdoor Heated Emergency Safety Shower

Hughes Safety Showers manufacture an Emergency Safety Shower with Eye/Facewash Fountain, trace tape heated and pre-insulated.

Pipework available in Galvanized or Stainless Steel.

As above but with extra heating EXP-AH-5G/45G. Also available without heating EXP-EJ-5G/45G.



OUTDOOR HEATED EMERGENCY SAFETY SHOWERS

- Designed in accordance with ANSI and EU guidelines
- Emergency Safety Shower with Eye/Facewash Fountain
- Insulated and trace tape heated for frost protection
- Hughes ball valve for greater reliability and longer life
- Available in Galvanised or Stainless Steel
- Choice of optional components including alarms and foot operation

Specification

The shower is operated by a pull handle for ease of use in an emergency. It has a removable self-draining overhead shower nozzle, which is specifically designed for high flow rates in line with ANSI and EU standards. The eye/facewash has high flow rate aerated diffusers for improved washing action to the eyes, face and hands and the 'unbreakable' eye/facewash fountain incorporates an integral lid connected to the water valve for automatic operation when the lid is pulled down.

The lid also ensures that the bowl remains clean and free from contamination at all times. The eye wash diffusers are fitted with fine mesh strainers and an individual flow controller and are designed to give a gentle flow of aerated water. The shower is pre-insulated with polyurethane foam to provide maximum insulation and has a corrosion resistant polyethylene outer jacket.

NB: Supplied in sections for assembly on site for economical shipping costs.

Hughes Ball Valve

- Designed using the latest 3D modelling software
- Specifically developed for Hughes Emergency Shower and Eye wash equipment
- Stainless steel construction to cope with the harshest atmospheres
- Low operating torque designed for ease of operation
- Tested and witnessed by independent test house specialist
- Designed for rough service

All valves are easily removable for servicing and maintenance.







PRODUCT INFORMATION SHEET





Outdoor Heated Emergency Safety Showers **EXP-EH-5G/45G**

EXP-AH-5G/45G, EXP-EJ-5G/45G

Outdoor Heated Emergency Safety Shower

MATERIALS OF CONSTRUCTION

| PIPEWORK & FITTINGS (G) | Galvanized Mild Steel with 150lb medium wall tubulars and fittings |
|------------------------------|---|
| PIPEWORK & FITTINGS (GS) | Stainless Steel 304L 150lb medium wall tubulars and fittings (316 available) |
| OPERATING VALVES | Hughes - 316 Stainless Steel |
| SHOWER SPRAY OUTLET | Hughes - Shower Nozzle Moulded Nylon 6 |
| EYE/FACEWASH FILTER STRAINER | Hughes - 316 Stainless Steel |
| INSULATION & OUTER CASING | Polyurethane Foam insulation with a Medium Density Polyethylene impact resistant Outer Casing |
| STANDARD FINISH | White with Green/White Safety Stripes (alternative colours available) |

SERVICES

| WATER INLET | 1 ¹ / ₄ " Male NPT |
|--------------------------------------|--|
| DESIGN OPERATING PRESSURE | 29 to 96 PSI (Higher supply pressures can be accommodated when incorporating the optional Pressure Regulating Valve) |
| HEATING TYPE | Trace Tape Heated and Pre-insulated |
| HEATING LOAD | 36 Watts (63 DVGW) |
| ELECTRICAL EQUIPMENT - Non Hazardous | Suitable for use in areas classified as Non-Hazardous |
| ELECTRICAL EQUIPMENT - Hazardous | ATEX Zone 1 & 2 |
| ELECTRIC SUPPLY | 240V Single Phase, 50/60Hz or 110V available |
| TEST PRESSURE | 149 PSI |
| FLOW RATES - ANSI | Shower: 76 liters/minute minimum |

ENVIRONMENTAL OPERATING TEMPERATURE

| MINIMUM AMBIENT OPERATING TEMP | -10° C (14° F) - EH -20° C (-4° F) - AH 0° C (32° F) - EJ |
|--------------------------------|---|
| MAXIMUM AMBIENT OPERATING TEMP | 35° C (95° F) - EH & EJ |

ACTIVATION/OPERATION

| SHOWER/BODY SPRAY OPERATION | Pull Handle |
|-----------------------------|---|
| EYE/FACEWASH OPERATION | Pull Lid (Treadle Foot control for hands-free - Optional) |

WEIGHTS and DIMENSIONS

| OVERALL DIMENSIONS | 13"(W) x 35"(D) x 91"(H) |
|--------------------|--------------------------|
| WEIGHT - UNPACKED | 35lb (No Options) |









PRODUCT INFORMATION SHEET






Outdoor Heated Emergency Safety Showers **EXP-EH-5G/45G**

EXP-AH-5G/45G, EXP-EJ-5G/45G

HUGHES G.A. DRAWING



HUGHES NORTH AMERICA INC



